

March 2, 2011



U.S. Department
of Transportation

East Building, PHH-30
1200 New Jersey Avenue S.E.
Washington, D.C. 20590

**Pipeline and Hazardous
Materials Safety Administration**

DOT-SP 12187
(FIFTH REVISION)

EXPIRATION DATE: December 31, 2014

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: ITW Sexton
(Former Grantee: Sexton Can Company, Inc.)
Decatur, AL
2. PURPOSE AND LIMITATIONS:
 - a. This special permit authorizes the manufacture, mark, sale and use of a non-DOT specification cylinder conforming with all regulations applicable to a DOT Specification 39 cylinder, except as specified herein, for the transportation in commerce of the materials authorized by this special permit. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
 - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.304a(a) in that the use of a non DOT specification package is not authorized, except as specified herein.
5. BASIS: This special permit is based on the application of ITW Sexton dated July 29, 2010, submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Material Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Compressed gas, n.o.s./ Refrigerant 407C (a ternary blend of HFC-32, HFC-125 and HFC-134a)	2.2	UN1956	N/A
Compressed gas, n.o.s./ Refrigerant 404A (an azeotropic blend of R-125, R-143a, and R-134a)	2.2	UN1956	N/A

NOTE: See paragraph 7.b(3) for commodity pressure limitations.

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Prescribed packaging is a non-DOT specification steel cylinder consisting of a seamless shell with the bottom attached by a mechanical seam. Construction must be in conformance with applicant's drawings numbers 995D0002 Rev. E dated October 27, 2006 and 995D0003 Rev. F dated October 27, 2006 on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA), and in conformance with the requirements of a DOT Specification 39 cylinder (§§ 178.35 and 178.65) except as follows:

§ 178.35(e) Safety Devices. The pressure relief system consists of a localized area of the bottom designed to fail at a minimum pressure of 357 psig and a maximum pressure of 571 psig. One cylinder must be taken from the beginning of production of each lot and pressurized until the relief system functions. If the system fails to function between 357 and 571 psig the lot represented by the test must be rejected.

§ 178.65(a) Type, size, service pressure and test pressure.

Each cylinder must be made from steel and have a seamless cylindrical body with the bottom attached by means of a circumferential mechanical joint.

(1) Water capacity may not exceed 32.5 cubic inches.
Maximum service pressure is 264 psig.

(2) Minimum test pressure is 357 psig.

* * * * *

§ 178.65(c) Manufacture.

(1) * * *

(2) * * *

(i) Mechanical joints must have strength equal to or greater than the minimum strength of the shell material in the finished cylinder.

* * * * *

§ 178.65(d) Wall thickness.

* * *. Wall thickness less than 0.0085 inch is not authorized.

* * * * *

§ 178.65(f) Pressure tests.

(1) Each cylinder must be tested to bring the internal temperature to 130° F or the pressure to 357 psig, whichever is higher.

* * * * *

(2)(ii) A failure initiates in a mechanical joint.

* * * * *

§ 178.65(i) Markings.

(2) * * *

(i) The cylinder must be marked "DOT-SP 12187" instead of "DOT-39".

* * * * *

March 2, 2011

(3) * * * . DOT-SP 12817 NRC 264/357 M * * * * .

b. OPERATIONAL CONTROLS:

(1) Filling density may not exceed 85 percent.

(2) The cylinder must be shipped in strong outside packagings in accordance with § 173.301(a)(9).

(3) The pressure of the lading at 70°F may not exceed 264 psig; and at 130°F, may not exceed 357 psig.

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.

b. A person who is not a holder of this special permit, but receives a package covered by this special permit, may reoffer it for transportation provided no modifications or changes are made to the package and it is offered for transportation in conformance with this special permit and the HMR.

c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this special permit must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by the Office of Hazardous Materials Special Permits and Approvals for a specific manufacturing facility.

e. A current copy of this special permit must be maintained at each facility where the package is manufactured under this special permit. It must be made available to a DOT representative upon request.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel, and cargo aircraft only.
10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel or aircraft used to transport packages covered by this special permit. The shipper must furnish a current copy of this special permit to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
 - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted

March 2, 2011

under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 Immediate notice of certain hazardous materials incidents, and 171.16 Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Dr. Magdy El-Sibaie
Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: MMToughiry/mb